

ase type a plus sign (+) inside this box -> [+]		App Patent and Trac	roved for use thro lemark Office U.S	PTO/SB/05 ugh 09/30/2000. OMB 0651 DEPARTMENT OF COMM	-0032 IERCE				
er the Paperwork Reduction Act of 1995, no persons are requir	_			plays a valid OMB control n	umber.				
UTILITY		Attorney Docket No. XM-0015							
PATENT APPLICATION		First Inventor or Application Identifier G Parsons							
TRANSMITTAL									
nly for new nonprovisional applications under 37 C.F R. § 1.53	(b)) Expres	s Mail Label No. EL	321954479US		سم <del>ر</del> 1				
APPLICATION ELEMENTS  see MPEP chapter 600 concerning utility patent application cont	tents.	ADDRESS TO			C S				
* Fee Transmittal Form (e.g., PTO/SB/17)	,	5. Microfich	e Computer Pro	gram ( <i>Appendix</i> )	4.5 				
(Submit an original and a duplicate for fee processing		6. Nucleotide and	or Amino Acid S	Sequence Submission	ပို့				
Specification [Total Pages   15 (preferred arrangement set forth below)	],	(if applicable, a	•		J				
- Descriptive title of the Invention		a. C	omputer Readal	ole Copy					
- Cross References to Related Applications		b. Pa	aper Copy (iden	tical to computer copy)					
- Statement Regarding Fed sponsored R & D		c. $\square$ si	atement verifyir	g identity of above copie	242				
- Reference to Microfiche Appendix									
Background of the Invention     Brief Summary of the Invention			ANYING APP	LICATION PARTS					
- Brief Description of the Drawings ( <i>if filed</i> )		7. Assignme	ent Papers (cove	er sheet & document(s))					
- Detailed Description		8. 37 C.F.R	.§3.73(b) Staten	Power of Attorney					
- Claim(s)			ore to are accepting	ment (if applicable)					
- Abstract of the Disclosure		1 3	on Disclosure	Copies of IDS	2				
Drawing(s) (35 U.S.C. 113) [Total Sheets 6	]	<b>₽</b> 7(  } }	nt (IDS)/PTO-14	1 1 '	,				
Oath or Declaration [Total Pages 3	1	11. Prelimina	ry Amendment						
a. X Newly executed (original or copy)		no i w i	eceipt Postcard	` '					
b. Copy from a prior application (37 C.F.I	R. § 1.63(d)	(Snoula t	ne specifically ite	•					
	pleted)	Jola Statemen	nt(s) Stat	ement filed in prior applic us still proper and desire					
I. DELETION OF INVENTOR(S) Signed statement attached de	eletina	(PTO/SB/C	09-12) Copy of Priority						
inventor(s) named in the prior a	pplication,		priority is claim						
see 37 C.F.R. §§ 1.63(d)(2) and NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SM	11.33(b).	15. Other:							
NOTE FOR TIEMS 1 & 13: IN ORDER TO BE ENTITLED TO FAT SM EES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.2 F ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.F	7), EXCEPT								
i, If a CONTINUING APPLICATION, check appropriate									
Continuation Divisional Continuation  Prior application information: Examiner	on-ın-part (Cl		ation No: oup / Art Unit:	<i>_</i>					
recontinuation information.  recontinuation or Divisional APPS only: The entire of the disclosure of the derence. The incorporation can only be relied upon when	accompanyi	the prior application, ng continuation or divi	from which an oa sional applicatio	n and is hereby incorporat	ed by				
	_	ICE ADDRESS	minueu nom me s	aubilitied application part	<b>.</b>				
Customer Number or Bar Code Label			or 🗶 Con	respondence address below	,				
***************************************	r No. or Attac	h bar code label here)							
me Benman & Collins									
dress 2049 Century Park East		<del></del>							
Suite 2740									
y Los Angeles	State	CA	Zıp Code	90067					
untry USA Telep	phone	(310) 553-2400	Fax	(310) 553-2675					
Name (Pant/Type) William J. Benman		Registration No.	(Attorney/Agent)	29,014	7				
Signature William Roy			Date	11/4/99	1				
(- 1400	fication und	er 37 CFR 1 10	Date	1 . 1 - ((1 )	J				
Express Mail No.EL321954479US	areagion und		sit: <u>      0 4  </u>	99					
I hereby certify that this correspondence is being d	enosited wir		, .		racea-				
service under 37 CFR 1 10 on the date indicated above and	d is addresse	d to the Assistant Com	missioner for Pate	nts, Washington, DC 2023.	108866 1				
Name of person mailing application: Yasmin Emerson		Signature of p	erson mailing app	olication: <b>U</b> - Eme	M				
				1					

EL321954479US PATENT XM – 0015

# SATELLITE DIGITAL AUDIO RADIO RECEIVER WITH INSTANT REPLAY CAPABILITY

G. Parsons C. Wadin

# SATELLITE DIGITAL AUDIO RADIO RECEIVER WITH INSTANT REPLAY CAPABILITY

5

#### **BACKGROUND OF THE INVENTION**

#### Field of the Invention:

10

15

20

25

The present invention relates to communications systems. More specifically, the present invention relates to satellite digital audio service (SDARS) receiver architectures.

While the present invention is described herein with reference to illustrative embodiments for particular applications, it should be understood that the invention is not limited thereto. Those having ordinary skill in the art and access to the teachings provided herein will recognize additional modifications, applications, and embodiments within the scope thereof and additional fields in which the present invention would be of significant utility.

#### Description of the Related Art:

Satellite radio operators will soon provide digital quality radio broadcast services covering the entire continental United States. These services intend to offer approximately 100 channels, of which nearly 50 channels will provide music with the remaining stations offering news, sports, talk and data channels. According to C. E. Unterberg, Towbin, satellite radio has the capability to revolutionize the radio industry, in the same manner that cable and satellite television revolutionized the television industry.

10

15

20

25

Satellite radio has the ability to improve terrestrial radio's potential by offering a better audio quality, greater coverage and fewer commercials. Accordingly, in October of 1997, the Federal Communications Commission (FCC) granted two national satellite radio broadcast licenses. The FCC allocated 25 megahertz (MHz) of the electro-magnetic spectrum for satellite digital broadcasting, 12.5 MHz of which are owned by CD Radio and 12.5 MHz of which are owned by the assignee of the present application "XM Satellite Radio Inc.". The FCC further mandated the development of interoperable receivers for satellite radio reception, i.e. receivers capable of processing signals from either CD Radio or XM Radio broadcasts. The system plan for each licensee presently includes transmission of substantially the same program content from two or more geosynchronous or geostationary satellites to both mobile and fixed receivers on the ground. In urban canyons and other high population density areas with limited line-ofsight (LOS) satellite coverage, terrestrial repeaters will broadcast the same program content in order to improve coverage reliability. Some mobile receivers will be capable of simultaneously receiving signals from two satellites and one terrestrial repeater for combined spatial, frequency and time diversity, which provides significant mitigation against multipath and blockage of the satellite signals. In accordance with XM Radio's unique scheme, the 12.5 MHz band will be split into 6 slots. Four slots will be used for satellite transmission. The remaining two slots will be used for terrestrial re-enforcement.

In accordance with the XM frequency plan, each of two geostationary Hughes 702 satellites will transmit identical or at least similar program content. The signals transmitted with QPSK modulation from each satellite (hereinafter satellite1 and satellite2) will be time interleaved to lower the short-term time correlation and to maximize the robustness of the signal. For reliable reception, the LOS signals transmitted from satellite1 are received, reformatted to Multi-Carrier Modulation (MCM) and rebroadcast by non-line-of-sight (NLOS) terrestrial repeaters. The assigned 12.5 MHz bandwidth (hereinafter the "XM" band) is partitioned into two equal ensembles or

program groups A and B. The use of two ensembles allows 4096 Mbits/s of total user data to be distributed across the available bandwidth. Each ensemble will be transmitted by each satellite on a separate radio frequency (RF) carrier. Each RF carrier supports up to 50 channels of music or data in Time Division Multiplex (TDM) format. With terrestrial repeaters transmitting an A and a B signal, six total slots are provided, each slot being centered at a different RF carrier frequency. The use of two ensembles also allows for the implementation of a novel frequency plan which affords improved isolation between the satellite signals and the terrestrial signal when the receiver is located near the terrestrial repeater.

A need has been recognized in the art for an ability to provide a listener with the capability of replaying a selection received via the SDARS receiver.

#### SUMMARY OF THE INVENTION

15

20

25

10

5

The need in the art is addressed by the system and method of the present invention. In a most general embodiment, the system is implemented as a receiver adapted to receive a transmitted signal and provide an instantaneous output signal in response thereto. The inventive receiver includes the medium (electronic or physical) for storing at least a portion of the received signal. In accordance with present teachings, the inventive receiver selectively outputs either a stored selection or the receive signal in response to user input (i.e. a replay signal).

In the illustrative embodiment, the receiver is a satellite digital audio radio service receiver having a radio frequency tuner and audio decoder. The system controller is a microprocessor that causes the system to store each selection as it is received. In the best mode, this is facilitated by the transmission and receipt of a start of selection signal and

an end of selection signal. The replay signal is provided via a user interface. Software running on a microprocessor includes code for detecting the presence of the instant replay signal. On detection of the replay signal, the software causes the system to output the stored selection.

5

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an illustrative implementation of a satellite digital audio service system receiver architecture constructed in accordance with the teachings of the present invention.

Fig. 2 is a diagram which illustrates the system of Fig. 1 in greater detail.

Fig. 2a is a diagram of an illustrative bitstream used by the satellite digital audio radio receiver with instant replay capability of the present invention.

Fig. 3 is a simplified block diagram of an illustrative implementation of a satellite digital audio radio service receiver incorporating the teachings of the present invention.

Fig. 4 is a detailed block diagram of the illustrative implementation of the receiver of Fig. 3.

20

15

Fig. 5 is a flow chart illustrative of the instant replay method of the present invention implemented in software and run by the microprocessor of the system controller of the satellite digital audio receiver with instant replay capability of the present invention.

10

15

20

25

#### DESCRIPTION OF THE INVENTION

Illustrative embodiments and exemplary applications will now be described with reference to the accompanying drawings to disclose the advantageous teachings of the present invention.

An illustrative implementation of a satellite digital audio service (SDARS) system architecture is depicted in Fig. 1. The system 10 includes first and second geostationary satellites 12 and 14 which transmit line-of-sight (LOS) signals to SDARS receivers located on the surface of the earth. The satellites provide for interleaving and spatial diversity. The system 10 further includes plural terrestrial repeaters 16 which receive and retransmit the satellite signals to facilitate reliable reception in geographic areas where LOS reception from the satellites is obscured by tall buildings, hills, tunnels and other obstructions. The signals transmitted by the satellites 12 and 14 and the repeaters 16 are received by an SDARS receiver 20. The receiver 20 may be located in an automobile, handheld or in a stationary unit for home or office use. The SDARS receiver 20 is designed to receive one or both of the satellite signals and the signals from the terrestrial repeaters and combine or select one of the signals as the receiver output as discussed more fully below.

Fig. 2 is a diagram which illustrates the system 10 of Fig. 1 in detail with a single satellite and a single terrestrial repeater. Fig. 2 shows a broadcast segment 22 and a terrestrial repeater segment 24. In the preferred embodiment, an incoming bit stream is encoded into a time division multiplexed (TDM) signal using a coding scheme such as MPEG by an encoder 26 of conventional design. The TDM bit stream is upconverted to RF by a conventional quadrature phase-shift keyed (QPSK) modulator 28. The upconverted TDM bit stream is then uplinked to the satellites 12 and 14 by an antenna 30.

10

15

20

Those skilled in the art will appreciate that the present invention is not limited to the broadcast segment shown. Other systems may be used to provide signals to the satellites without departing from the scope of the present teachings.

The satellites 12 and 14 act as bent pipes and retransmit the uplinked signal to terrestrial repeaters 18 and portable receivers 20. As illustrated in Fig. 2, the terrestrial repeater includes a receiver demodulator 34, a de-interleaver and reformatter 35, a terrestrial waveform modulator 36 and a frequency translator and amplifier 38. The receiver and demodulator 34 downconverts the downlinked signal to a TDM bitstream. The de-interleaver and reformatter 35 reorders the TDM bitstream for the terrestrial waveform. The digital baseband signal is then applied to a terrestrial waveform modulator 36 (e.g. MCM or multiple carrier modulator) and then frequency translated to a carrier frequency prior to transmission.

In accordance with the present teachings, the digital baseband signal includes a number of audio selections along with a signal which indicates the beginning and end thereof. Fig. 2a is a diagram which shows what this digital signal might look like.

Fig. 2a is a diagram of an illustrative bitstream used by the satellite digital audio radio receiver with instant replay capability of the present invention. The bitstream a Service Control Header 40 and a content payload (not shown). The Service Control Header includes, *inter alia*, an Auxiliary Data Field 42. The Auxiliary Data Field 42 is a time multiplexed message structure which is used to carry the following information:

- · Service control and status information
- · Narrowcast Categories
- · Start/End of program
- · Program(Song) ID
- · Display information
- News ticker
- · Text associated with a program (e.g. streaming text)
- · Replacement text (TBC) (e.g. extended service label, song/artist label, etc.)
- Other text information (e.g. sports scores, weather, etc.)

30

25

10

15

20

25

The frequency-translated signal will be received by a number of satellite digital audio radio receivers such as that depicted in Fig. 3 below.

Fig. 3 is a simplified block diagram of an illustrative implementation of a satellite digital audio radio service receiver incorporating the teachings of the present invention. The receiver 20 includes an antenna 110, an RF tuner module 200, a digital audio storage media 700, an audio decoder 800, a system controller 500, and a user interface 1000. The interface 1000 is adapted to receive and instant replay input from a user via a suitable input device 1010. The input device 1010 may be a simple button or a microphone with voice recognition capability.

Fig. 4 is a detailed block diagram of the illustrative implementation of the SDARS receiver of Fig. 3. Fig. 4 shows that the receiver 20 further includes an antenna module 100, the antenna 110, the RF tuner module 200, a channel decoder 300, a source decoder 400, a digital control and status interface bus 600, the system controller 500, digital audio storage media 700, the audio decoder 800, a power supply 900, and the user interface 1000. The SDARS receiver is disclosed in accordance with the teachings of U.S. Patent Application No. \_\_\_\_\_\_\_, entitled Tuner Architecture for Satellite and Terrestrial Reception of Signals, filed \_\_\_\_\_\_ by P. Marko and A. Nguyen (Atty. Docket No. XM-0003), the teachings of which are incorporated herein by reference.

Returning to Fig. 3, in the illustrative embodiment, the digital audio storage media 700 is essentially a cycle buffer and may be optical, electronic or physical as will be appreciated by those of ordinary skill in the art. In the best mode, system controller 500 includes a microprocessor that causes the system to store each selection as it is received. In the illustrative embodiment, this is facilitated by the transmission and receipt of a 'start of selection' signal and an 'end of selection' signal. A replay signal is provided via the Instant Replay interface 1010 and, in accordance with present teachings, the inventive receiver selectively outputs either a stored selection or the receive signal in response thereto. As discussed more fully below, software running on a microprocessor includes

15

20

25

code for detecting the presence of the instant replay signal. On detection of the replay signal, the software causes the system to output the stored selection.

Fig. 5 is a flow chart illustrative of the instant replay method of the present invention implemented in software and run by the microprocessor of the system controller of the satellite digital audio receiver with instant replay capability of the present invention. As shown in Fig. 5, the flow chart 2000 begins with initialization of the radio at steps 2010 and 2012. At step 2014, the system checks to determine whether a broadcast channel has been selected. If not, the instant replay system remains inactive until a broadcast channel is selected.

At step 2016, on the selection of a broadcast channel, the system controller checks for the activation of the instant replay feature via the instant replay interface 1010 via the user interface 1000. If the instant replay feature has been activated, at step 2018, the system controller 500 routes stored digital audio from the digital audio storage media 700 to the audio decoder 800 for output via the speaker 860.

If, at step 2016, the instant replay feature has not been activated, then, at step 2020, the system controller 500 routes received digital audio from the tuner 200 to the audio decoder 800 for output via the speaker 860.

Next, at step 2022, the system controller 500 is commanded to check for the receipt of a 'start of selection' indication. On receipt of the start of selection indication, at step 2024, the system controller 500 activates the digital audio storage media 700 and routes the selection being received by the tuner 200 thereto. The system controller 500 continues to stream the received digital audio to the storage media 700 until, at step 2026, the system controller 500 is commanded to check for the receipt by the tuner 200 of an end of selection signal. On receipt of the end of selection signal, at step 2028, the system controller 500 ends storage of the received digital audio stream. Thereafter, the system checks whether the broadcast channel is still selected at step 2014, and, if so, awaits the next activation of the instant replay feature at step 2016.

10

15

Thus, the present invention has been described herein with reference to a particular embodiment for a particular application. Those having ordinary skill in the art and access to the present teachings will recognize additional modifications, applications and embodiments within the scope thereof. For example, plural media storage devices or areas within a single device may be employed to store more than a single selection that time or to store information being received on one ensemble while the user is listening to another ensemble. Further, those skilled in the art will appreciate that the information may be encoded and/or compressed prior to storage to minimize the stored requirement and/or maximize system performance without departing from the scope of a present teachings.

It is therefore intended by the appended claims to cover any and all such applications, modifications and embodiments within the scope of the present invention.

Accordingly,

#### WHAT IS CLAIMED IS:

#### **CLAIMS**

1. A receiver comprising:

first means for receiving a transmitted signal and providing an instantaneous output signal in response thereto;

second means for storing at least a portion of said received signal;

third means for providing a replay signal; and

fourth means for selectively outputting said stored portion of said received signal or said instantaneous output signal in response to said replay signal.

- 2. The invention of Claim 1 wherein said first means includes a radio frequency tuner.
  - 3. The invention of Claim 2 wherein said first means includes an audio decoder.
  - 4. The invention of Claim 1 wherein said third means includes a user interface.
  - 5. The invention of Claim 1 wherein said fourth means as a system controller.
- 6. The invention of Claim 5 wherein said system controller includes a microprocessor.
- 7. The invention of Claim 6 wherein said fourth means includes software running on said microprocessor.

- 8. The invention of Claim 7 wherein said software includes code for detecting the presence of said instant replay signal.
- 9. The invention of Claim 8 wherein said software includes code for causing said receiver to output said stored portion of said received signal on the detection of said instant replay signal.
- 10. The invention of Claim 9 wherein said software includes code for causing said receiver to output said instantaneous output signal on a failure to detect said instant replay signal.
- 11. The invention of Claim 10 wherein said transmitted signal includes a start of selection signal and an end of selection signal and said software includes code for detecting said start of selection signal and said end of selection signal.
- 12. The invention of Claim 11 wherein said software includes code for activating said second means in response to detection of said start of selection signal.
- 13. The invention of Claim 12 wherein said software includes code for deactivating said second means in response to detection of said end of selection signal.
- 14. The invention of Claim 7 wherein said software includes code for detecting the selection of a broadcast channel.

- 15. A satellite digital audio receiver comprising:
- a radio frequency tuner and an audio decoder for receiving a transmitted signal and providing an instantaneous output signal in response thereto;
  - a storage medium for storing at least a portion of said received signal;
  - a user interface for providing a replay signal; and
- a system controller for selectively outputting said stored portion of said output signal or said instantaneous output signal in response to said replay signal.
- 16. The invention of Claim 15 wherein said system controller includes a microprocessor.
- 17. The invention of Claim 16 wherein said system controller includes software running on said microprocessor.
- 18. The invention of Claim 17 wherein said software includes code for detecting the presence of said instant replay signal.
- 19. The invention of Claim 18 wherein said software includes code for causing said audio decoder to output said stored portion of said received signal on the detection of said instant replay signal.
- 20. The invention of Claim 19 wherein said software includes code for causing said audio decoder to output said instantaneous output signal on a failure to detect said instant replay signal.

- 21. The invention of Claim 20 wherein said transmitted signal includes a start of selection signal and an end of selection signal and said software includes code for detecting said start of selection signal and said end of selection signal.
- 22. The invention of Claim 21 wherein said software includes code for causing said system controller to store said instantaneous output signal in said storage medium in response to detection of said start of selection signal.
- 23. The invention of Claim 22 wherein said software includes code for causing said system controller to stop storing said simultaneous output signal in said storage medium in response to detection of said end of selection signal.
- 24. The invention of Claim 17 wherein said software includes code for detecting the selection of a broadcast channel.
- 25. A method for receiving a satellite digital audio signal including the steps of: receiving a transmitted signal and providing an instantaneous output signal in response thereto;

storing at least a portion of said received signal;

providing a replay signal; and

selectively outputting said stored portion of said output signal or said instantaneous output signal in response to said replay signal.

- 26. The invention of Claim 25 including the step of detecting the presence of said instant replay signal.
- 27. The invention of Claim 26 including the step of causing said receiver to output said stored portion of said received signal on the detection of said instant replay signal.
- 28. The invention of Claim 27 including the step of causing said receiver to output said instantaneous output signal on a failure to detect said instant replay signal.
- 29. The invention of Claim 28 wherein said transmitted signal includes a start of selection signal and an end of selection signal and said method includes the step of detecting said start of selection signal and said end of selection signal.
- 30. The invention of Claim 29 including the step of activating said second means in response to detection of said start of selection signal.
- 31. The invention of Claim 30 including the step of deactivating said second means in response to detection of said end of selection signal.
- 32. The invention of Claim 25 including the step of detecting the selection of a broadcast channel.

10

#### ABSTRACT OF THE DISCLOSURE

A receiver adapted to receive a transmitted signal and provide a replay capability in response thereto. The inventive receiver includes the medium (electronic or physical) for storing at least a portion of the received signal. In accordance with present teachings, the inventive receiver selectively outputs either a stored selection or the receive signal in response to user input (i.e. a replay signal). In the illustrative embodiment, the receiver is a satellite digital audio radio service receiver having a radio frequency tuner and audio decoder. The system controller is a microprocessor that causes the system to store each selection as it is received. In the best mode, this is facilitated by the transmission and receipt of a start of selection signal and an end of selection signal. The replay signal is provided via a user interface. Software running on a microprocessor includes code for detecting the presence of the instant replay signal. On detection of the replay signal, the software causes the system to output the stored selection.






FIG 1

メネーとス



ě

FIG 3



Please type a plus sign (+) inside this box   PTO/SB/01 (12-97)  Approved for use through 9/30/00. OMB 0651-0032  Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  a valid OMB control number.										
		Attorney Dock	et Number	XM-0015						
DECLARATION FOR UDESIGN	First Named In	ventor	G. Parsons							
PATENT APPLICA	C	COMPLETE IF KNOWN								
(37 CFR 1.63	3)	Application Nur	nber	/						
☑ Declaration ☐ Decla		Filing Date								
Submitted OR Subm	Declaration Submitted after Initial Filing (surcharge	Group Art Unit								
	FR 1.16 (e))	Examiner Name	•							
As a below named inventor, I hereby declare that:  My residence, post office address, and citizenship are as stated below next to my name.  I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled SATELLITE DIGITAL AUDIO RADIO RECEIVER WITH  INSTANT REPLAY CAPABILITY  the specification of which  (Title of the Invention)  is attached hereto  OR  was filed on (MM/DD/YYYY)  and was amended on (MM/DD/YYYY)  I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.  I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1 56.										
I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.										
Prior Foreign Application Number(s) Co	ountry	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached? YES NO						

Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto: I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Filing Date (MM/DD/YYYY)

Application Number(s)

[Page 1 of 2]
Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

PTO/SB/01 (12-97)  Please type a plus sign (+) inside this box   Approved for use through 9/30/00. OMB 0651-0032  Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.
---

## **DECLARATION** — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.														
U.S. Parent Application or PCT Parent Number					Parent Filing Date (MM/DD/YYYY)			Parent Patent Number (if applicable)						
Additional	IU.S or F	PCT international	applica	tion nur	mbers a	re listed on	a sup	plemental	priority data	sheet P	TO/SB/	02B attached h	ereto.	
As a named inv	ventor, I h	ereby appoint th	e follow	ıng regi:	stered p	ractitioner(s	s) to p	rosecute t	this application	on and to	transa			
and Irademark	Office co	onnected therew	th:	Custor OR	ner Nun	nber				<del></del>	<b>&gt;</b>	Place Custo Number Bar		
		···	X				name	/registration	on number lis	sted belo	<sub>w</sub> L	Lahel he	re	
İ	Name	e				stration mber			Nam			stration mber		
William J				29.0	014	IIDEI		<del>                                     </del>				Illinei		
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,														
Additional	registered	d practitioner(s) r	named c	n supp	lementa	J Registered	d Prac	titioner In	formation she	eet PTO	/SB/020	Cattached here	eto.	
Direct all correspondence to: Customer Number or Bar Code Label  OR Correspondence address below									ress below					
Name	Willi	am J. Benr	nan								***************************************			
Address	Benn	nan & Coll	lins											
Address	2049	Century P	ark E	ast, S	Suite	2740								
City	<del> </del>	Angeles					s	State CA ZII			900	· · · · · · · · · · · · · · · · · · ·		
Country	USA			Te	elepho	ne (310	) 55	$) 553-2400 \qquad  _{Fax}   (3)$			(310	310) 553-2675		
believed to be punishable by	true; and fine or in	It statements mad further that the apprisonment, or t issued thereon.	ese stat both, u	ements	were n	nade with th	he kno	owiedge t	that willful fal	lse state	ements	and the like so	made are	
Name of So	ole or F	irst Invento	r:	-				A petition	n has been	filed fo	r this u	ınsigned inve	ntor	
Gı	ıven Nar	ne (first and m	iddle [i	f any])			Family Name or Surname							
Gary							Parsons							
Inventor's Signature											Date			
Residence: (	City	Potomac			State MD			ountry	untry US			Citizenship	US	
Post Office A	ddress	11009 Sta	ınmoı	re Dr	ive									
Post Office A	ddress													
City		Potomac	State	MD	,	ZIP	20	0854		Cou	ntry	US		
Additional	invento	re are being no	amed a	n tha	1	nnlomonto	A A Ale	ditional li	nuontario) a	'م/احمط	DTO	CD/OOA ottoo	la a el la a esta e	

Please type a plus sign (+) inside this box ->	+	

PTO/SB/02A (3-97)

Approved for use through 9/30/98 OMB 0651-0032

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

### **DECLARATION**

### **ADDITIONAL INVENTOR(S)** Supplemental Sheet Page 1 of 1

Name of Additional Joint Inventor, if any:  A petition has been filed for this unsigned inventor											
Given Name (first and middle [if any])					Family Name or Surname						
Craig Wadin											
Inventor's Signature								Date			
Residence: City	Sunrise	State	FL		Country	US		Citizens	hip	US	
Post Office Address	11015 NW 27th Street										
Post Office Address											
City	Sunrise	State	FL		ZIP .	33322	Countr	y US			
Name of Addition	nal Joint Inventor, if ar	ny:			A petitic	on has been file	d for th	is unsigr	ned inv	entor	
Given Na	me (first and middle [if any	/])				Family Nar	ne or S	Surname			
Inventor's Signature								Da	te		
Residence: City		State			Country			Citize	nship		
Post Office Address											
Post Office Address											
City		State			ZIP		Cour	ntry			
Name of Addition	nal Joint Inventor, if ar	ny:			A petitic	on has been filed	d for th	nis unsigr	ned inv	entor	
Given Name (first and middle [if any]) Family Name or Surname											
Inventor's Signature								Da	te		
Residence: City		State			Country			Citize	nship		
Post Office Address											
Post Office Address	<u> </u>										
City		State			ZIP		C	ountry			

Burden Hour Statement: This form is estimated to take 0.4 hours to complete Time will vary depending upon the needs of the individual case. Any comments on the amount of time, you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.